

HUAWEI IdeaHub Board Pro

Smooth | Simple | Sleek




Product Highlights

Optical Light Protection, Eliminating Color Cast

4K UHD anti-blue light feature, certified by TÜV Rheinland, for optimal eye comfort.

Customized colors, anti-glare design, delivering vivid and eye-protective images.

7H Mohs tempered glass screen that is pressure- and impact-resistant.





Huawei Projection, Effortless Sharing

App free projection supported by Huawei phones running EMUI 10.1.1 or later (app download not necessary when connected to the same network).

Multiple projection modes and up to 4K 30 fps UHD image sharing.

Reverse control and dual-screen real-time interaction.

Co-authoring and real-time annotation, supporting batch saving and QR code scanning to take away content.

Smart Pen, Seamless Writing

Intelligent recognition of languages and graphics with an accuracy up to 95%.

Diverse, user-friendly writing and erasing modes.


Zero gap on screen lamination and 35 ms ultra-low latency.



Application Scenarios

Multi-person open discussion





Extended screen for Meeting

Smart classroom



HUAWEI IdeaHub Board Pro



Components

Main body

Codec, microphone array, and speaker

Rolling stand

Optional (65") Optional (86")



Screen

Optical anti-blue light Supported

Color gamut 90% NTSC

Anti-glare Supported

Number of touch points 20

IdeaHub Board Pro 65

Model IFP-UG65

Package dimensions

Width: 1650 mm Height: 1050 mm Depth: 210 mm

Product dimensions

Width: 1486.5 mm Height: 908.6 mm Depth: 89.1 mm

Gross weight 54 kg

Net weight 43 kg

io ng

IdeaHub Board Pro 86

Model IFP-UG86

Package dimensions

Width: 2090 mm Height: 1375 mm Depth: 280 mm

Product dimensions

Width: 1963.8 mm Height: 1176.1 mm Depth: 95 mm

Gross weight 98 kg

Net weight 77 kg

Notes: Actual dimensions may vary according to configuration, manufacturing process, and measurement method.

Stylus pen

2

Wall mount bracket Optional (65"), standard (86")



Cables

Network and power cables

IdeaShare Key Optional



Resolution 4K

Brightness ≥400cd/m2

Backlight type D-LED

Glass hardness 7H Mohs Viewing angle Horizontal: $\geq 178^{\circ}$, vertical: $\geq 178^{\circ}$

Automatic brightness adjustment Supported

Refresh rate 60 Hz

Screen lamination Zero gap on screen lamination

Writing

	Erasing by hand gestures Supported Writing latency ≤35 ms	Smart writing Support for recognition of English, Chinese, and 11 graphics	Precision ±1 mm
		Whiteboard saving mode QR code scanning, email, local, and USB flash drive	
Proje	ction		
	Projection mode	Wireless projection effect	Wired projection effect
	App free projection, DLNA projection, wired projection, and projection using app and IdeaShare Key	4K30fps	4K60fps
Meet	ing		
	Meeting type	Video effect	Presentation sharing
	Support for third-party remote meetings, compatible with Zoom, Teams, and Webex	1080p 30 fps video meeting delivered by Huawei-recommended cameras (optional)	1080p HD presentation sharing
Spea	kers		
	Frequency domain	Quantity	Stereo
	20 Hz to 20 kHz	4	Supported
Micro	ophones		
	Sound pickup distance 8 m	Sound pickup angle 180° front view	Quantity 2
	Frequency domain 20 Hz to 20 kHz	Enhanced functions Echo cancellation, noise suppression, automatic gain control, support for external microphones	
Came	era	ernal cameras recommended by Huawei.	

System

CPU 4Core@1.5G

RAM 8 GB

Flash 64 GB

Operating system

Android 9.0 and Windows 10(i3*/i5/i7, optional)

Communications Protocols

Network transmission protocols

TCP/IP, DHCP, DNS, SMTP, SNMP, SNTP, Telnet, SSH, HTTP, HTTPS, TR-069

Others

Fault self-check

Supported

Wi-Fi standards

IEEE 802.11 a/b/g/n/ac/w, IEEE 802.1x, WPA2, Wi-Fi AP and Station modes

IP protocols

IPv4 and IPv6 dual stacks

Language

10 language such as simplified Chinese and English*

Ports

Video input

Audio output

2 x HDMI, 1 x Type-C port, 1 x optional OPS input

Video output

1 x built-in screen, 1 x HDMI

Other ports

2 x USB A port, 1 x USB B port, 1 x Type-C port, 1 x RJ45 (10/100/1000 M LAN), 1 x RJ45 serial port

Audio input

2 x built-in microphone array, 1 x 3.5 mm LINE IN, 1 x optional OPS audio input, 2 x HDMI audio input **

Wi-Fi

2.4 GHz, 5 GHz

4 x built-in speakers, 1 x 3.5 mm LINE OUT, 1 x HDMI (audio output)

Electrical Characteristics

Voltage	Frequency	Max. power
100-240 V AC	50 Hz to 60 Hz	< 350 W (65") < 450 W (86")

Environment Requirements

≤46dBA SPL

Noise

Operating altitude < 5000 m

> 200 lux

Temperature

0°C to 40°C (operating state) -20°C to 60°C (non-operating state)

Relative humidity

Recommended illuminance

10% to 95% (operating state) 0% to 95% (non-operating state) Min. illuminance

7 lux

Learn More>>>

Huawei Intelligent Collaboration Website



Copyright © Huawei Technologies Co., Ltd. 2021. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

W HUAWEI, HUAWEI, and **W** are trademarks or registered trademarks of Huawei Technologies Co., Ltd. All other trademarks, product names, service names, and company names mentioned in this document are the property of their respective holders.

Disclaimer

The technical specifications described in this document include but are not limited to parameters and performance indicators and vary depending on the actual release. This document does not constitute a warranty of any kind, expressed or implied. Huawei may update relevant information from time to time. Huawei reserves the right to update or correct the information about related products or solutions. For details, see the latest release notes or introduction. Updated: April 2021 Huawei Technologies Co., Ltd. Huawei Industrial Base, Bantian, Longgang, Shenzhen Tel: 86-755-28780808 Post code: 518129